

### **AMENDMENTS TO THE SPECIFICATION**

Please delete the section entitled "SUMMARY OF THE INVENTION" in its entirety and substitute the following section therefor:

#### **SUMMARY OF THE INVENTION**

[0020.1] The present invention, among other applications, is directed to solving these and other problems and disadvantages of the prior art. The present invention provides a superior technique for performing cryptographic operations within a microprocessor. In one embodiment, an apparatus for performing cryptographic operations is provided. The apparatus includes an x86-compatible microprocessor. The x86-compatible microprocessor has an instruction register having a ~~cryptographic instructions~~single, atomic cryptographic instruction disposed therein, a keygen unit, and an execution unit. The instruction register is within the x86-compatible microprocessor and has a ~~cryptographic instructions~~single, atomic cryptographic instruction disposed therein. The ~~cryptographic instructions~~single, atomic cryptographic instruction is part of an application program, and the x86-compatible microprocessor executes the application program. The ~~cryptographic instructions~~single, atomic cryptographic instruction prescribes one of the cryptographic operations, is arranged according to the instruction format for execution on the x86-compatible microprocessor, and also prescribes that a user-generated key schedule be employed when executing the one of the cryptographic operations. The keygen unit is operatively coupled to the instruction register. The keygen unit directs the x86-compatible microprocessor to load the user-generated key schedule. The execution unit is operatively coupled to the keygen unit. The execution unit employs the user-generated key schedule to execute the one of the cryptographic operations. The execution unit includes a cryptography unit that is configured execute a plurality of cryptographic rounds on each of a plurality of input text blocks to generate a corresponding each of a plurality of output text blocks, where the plurality of cryptographic rounds are prescribed by a control word that is provided to the cryptography unit.

[0021] One aspect of the present invention contemplates an apparatus for performing cryptographic operations. The apparatus has a cryptography unit within a x86-compatible microprocessor and a keygen unit. The cryptography unit executes one of the cryptographic operations responsive to receipt of a ~~cryptographic instruction~~single, atomic cryptographic instruction within an application program that prescribes the one of the cryptographic operations, where the ~~cryptographic instruction~~single, atomic cryptographic instruction is arranged according to the instruction format for execution on the x86-compatible microprocessor, and where the x86-compatible microprocessor executes the application program. The ~~cryptographic instruction~~single, atomic cryptographic instruction also prescribes that a user-generated key schedule be employed when executing the one of the cryptographic operations. The keygen unit is operatively coupled to the cryptography unit. The keygen unit directs the x86-compatible microprocessor to perform the one of the cryptographic operations and to employ the user-generated key schedule when performing the one of the cryptographic operations.

[0022] Another aspect of the present invention provides a method for performing cryptographic operations in a x86-compatible microprocessor. The method includes executing an application program that is stored in memory, where the executing includes receiving a ~~cryptographic instruction~~single, atomic cryptographic instruction from the memory that prescribes employment of a user-generated key schedule during execution of one of a plurality of cryptographic operations and within a cryptographic unit in the x86-compatible microprocessor. The ~~cryptographic instruction~~single, atomic cryptographic instruction is arranged according to the instruction format for execution on the x86-compatible microprocessor. The method also includes employing the user-generated key schedule when executing the one of the cryptographic operations to generate a result of the one of the cryptographic operations.